



Model: CSI 20-2EF1T-U1116
COSD: XXX
Summary description: 20VA Industrial Quality Sine Wave Inverter
 24Vdc to 230Vac/50Hz
Customer Name: Thiele KG/Germany
Customer Part Number: Same as above

Product description:

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. The use of high frequency conversion enables a compact construction, low weight and high efficiency. The unit has full electronic protection. The input and output are filtered for low noise. Cooling is by natural convection. The use of components with established reliability results in high MTBF. The unit is manufactured at our plant under strict quality control.

Special Features: Conformal coating. Actual load is 4-5VA

SPECIFICATIONS

Input Voltage

24Vdc nominal
 21-29Vdc operating range
 Input current: 1.2A max

Input Protection

Reverse polarity protection
 Internal safety fuse
 Lower voltage than the specified minimum input will not damage the unit

Isolation

500Vdc input to chassis
 500Vdc input to output
 500Vdc output to chassis

Standards

Designed to meet EN 60950-1 and corresponding standards

EMI

EN55032 Class A with margins

Output Voltage

230Vac, 0.1Arms, 50Hz
 Output is floating

Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

± 3% from no load to full load

Load Crest Factor

2 at 90% load

Output Noise

High frequency ripple is better than 100mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection.

Output Overvoltage Protection

270V by internal supply voltage limiting

Efficiency

80% at full load

Operating Temperature Range

0°C to +50°C for full specifications

Temperature Drift

0.05% per °C over operating temperature range

Cooling

By natural air convection

Environmental Protection

Basic ruggedizing
 Conformal coating

Shock / Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

150,000 hours at 45°C

Indicators

None

Control Input

None

Alarm Output

Not installed

Package Dimensions (W x H x L)

F1: 112 x 51 x 201mm
 (4.4" x 2" x 7.9")

Mounting holes are clear

Weight

0.8kg (1.8 lb)

Connections

9-pole barrier type terminal block with 3/8" spacing. Snap-on cover included

RoHS Compliance


Compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-Out

115VAC OUTPUT			DC INPUT					
NOT USED	L ₁	L ₂	NOT USED	NOT USED	NOT USED	GND	+	-
1	2	3	4	5	6	7	8	9

Originated by TS/kv	Date Nov 29, 2021
Updated by TS	Drawing No./ Rev. SCD U1116A
Approved by TS	

This document is the property of Absopulse Electronics Ltd. Its contents are proprietary and may neither be copied, reproduced, nor its contents disclosed to others without prior written agreement from Absopulse Electronics Ltd.