

Model: FTT2K5-E3P/S3P-3U7A-U2884
COSD: 67X4-1
Summary description: 2.5kVA Industrial Quality Frequency Converter
 400Vac, 3-phase to 115Vac (L-L) 3-phase, 400Hz
Customer Name: Thiele KG/Germany
Customer Part Number: Same as above



Product description:

This rugged, industrial quality DC/AC inverter utilizes field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The inverter is built with internal power modules. One FIB380, three KHH2000 modules convert the input voltage to an internal DC bus voltage, which feeds three MSI 1500 output modules. High frequency conversion enables a compact construction, low weight and high efficiency. The input and output are filtered for low noise. High quality built-in fans provide sufficient airflow for operation without de-rating within the specified temperature range. The fans draw air into the unit, and exhaust at the terminal side of the unit. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also ensures exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headrooms, and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

Special Features: Conformal coating, Alarm

SPECIFICATIONS

Input Voltage
 400Vac, 3-phase, 47-63Hz
 360-440Vac operating range
 Input Current: 6.5Arms max. per phase

Input Protection
 Inrush current limiting
 Varistor
 Internal safety fuses
 Lower voltage than the specified minimum input will not damage the unit

Isolation
 2250Vdc input to chassis/output
 2250Vdc output to chassis



Standards
 Designed to meet
 C22.2 No. 107.1 - 01,
 UL 458 and EN62368-1

EMI
 EN 55032 Class A with margins

Switching Frequency
 55kHz ±3kHz

Output Voltage
 115Vac (L-L), 3-phase, 400Hz
 66Vac (L-N)
 13Arms per phase
 Output neutral is internally connected to chassis

Output Wave Form
 Sinusoidal



Total Harmonic Distortion
 Better than 5% at full load

Line/Load Regulation
 ±6% combined from no load to full load

Output Noise
 Better than 500mVrms
 (20MHz BW)

Output Overload Protection
 Current limiting with short circuit protection
 Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection
 By internal supply voltage limiting at 140Vac L-L

Efficiency
 Typically 80% at full load

Operating Temperature Range
 0°C to 50°C for full specification

Temperature Drift
 0.05% per °C over operating temperature range

Cooling
 By built-in high quality fans

Environmental Protection
 Basic ruggedizing
 Conformal coating

Shock/Vibration
 IEC 61373 Cat 1 A&B

Humidity
 5 - 95% non-condensing

MTBF
 90,000 hours @ 45°C (Fans not included)
 Demonstrated MTBF is significantly higher

Indicators
 None

Control Input
 None

Alarm Output
 Output Fail Alarm on each output phase
 Form C contacts


Package/Dimensions
 3U7: 432 x 132x 407mm
 (17" x 5.2" x 16")
 Chassis mount

Weight
 12kg (26 lbs)

Connections
 Input: 3-pole terminal block Phoenix FRONT
 Output: 4-pole terminal block, 13mm spacing
 Alarm: 3-pole Phoenix FRONT2.5-V-SA10

RoHS Compliance
 Compliant

Warranty
 Two years subject to application within good engineering practice
 Contamination related failures and shipping cost excluded

Originated by TS/kv	Date April 28, 2023
Updated by TS/kv	Drawing No./ Rev. SCD 67X4 1000A1
Approved by TS	

This document is the property of Absopulse Electronics Ltd. Its contents are proprietary and may neither be copied, reproduced, nor its contents disclosed to others without prior written agreement from Absopulse Electronics Ltd.